superbrightleds.com | Even-Glow®

Even-Glow COB LED Strips

RGB+CCT COB Strip Specifications

Project _____ Date _____

Notes _____

Voltage 24 VDC | COB LEDs | RGB+ Tunable White | High CRI 90+ | IP20 | 5yr WARRANTY

Available Models[1]

☐ STN-B-F90-O35A-12Z5M-24V

SAMPLE PART NUMBER BREAKDOWN

STN-B-F90-O35A-12Z5M-24V

Series	Type	CRI	LED Type	LEDs/Segment	IP Rating	Width	Density	Length	Voltage
STN-B	F	90	O	35	A	12	Z	5M	24V
Non-weatherproof	RGB+CCT	90+ CRI	COB	35 LEDs/seg	IP20	12mm	840 LEDs/m	5 meters	24 VDC

Overview

The Even-Glow® Series 5m RGB+CCT COB LED Strip Light uses a high density chip-on-board (COB) LEDs to create a smooth, seamless line of light ideal for use on or around reflective surfaces such as granite countertops and tile floors. The strip provides a range of vibrant RGB colors and tunable white. Easily customize the strip using the cut segments every 1.65 inches. Flexible construction and 3M™ adhesive backing make it easy to install on flat and round surfaces and edges. Pair with a controller (sold separately) to customize color tone and settings.

Features

- COB LEDs create seamless line of light - no visible hotspots
- Flexible, cuttable, and 3M™ adhesive-backed for easy install
- Smooth color blending and saturation of RGB colors
- Tunable White CCT range: 2700K-6500K
- High density design with 256 LEDs/ft
- 0-100% PWM dimmable

Product Details

- Class 2 Max Run: 16.4ft (5m)
- Cut Segment Length: 42mm (1.65in.)
- Strip Width: 12mm (0.47in.)
- Pigtail connection
- 24 VDC input

Certifications and Compliances

- UL Listed - UL 2108 (IFDR)
- CE compliant

UL® LISTED CE

Applications

- Accent Lighting
- Cove Lighting
- Displays
- Sign Lighting
- Stage & Theaters
- Toe Kick Lighting
- Trade Shows
- Under-Cabinets

Warranty

- 5-year warranty

T 866.811.5550 | **F** 314.972.6202
https://www.superbrightleds.com
email: commercial-sales@superbrightleds.com

[1]Contact customer service if interested in other options.

Rev. V1.1 Date: 12/20/2025

Specifications are subject to change without notice.

Even-Glow COB LED Strips

RGB+CCT COB Strip Specifications

Installation Instructions

1. Plan Your Layout

Identify COB strip placement, including how long each run will be and where to place the power supply. Depending on how evenly you want the light to appear, decide on a straight run, center feed, loop-back, or multi-leg. Hidden placements like under cabinets or inside coves produce indirect illumination for ideal lighting results.

2. Match the Power Supply

First, calculate the total strip wattage by multiplying the total strip length by the power used per foot for the total strip wattage. Next, use the following formula to determine the minimum necessary wattage of your power supply

Total Strip Wattage / 0.80 = Minimum Power Supply Wattage

Round up to the nearest wattage, and this number will provide you with the 20% wattage overhead required to maintain power supply longevity.



3. Cutting the Strip

If you need to cut the strip to a custom length, unroll the strip and find the marked cut points, usually between copper pads. Make sure the strip is not powered when cutting. Use sharp scissors to cut only on these lines. Cutting anywhere else can break the circuit.

4. Connecting the Strip (Solderless or Soldering)

To connect cut sections of LED strips to a power supply or controller, wires can be soldered directly to the copper pads or solderless connectors may be used as an alternative. To use a solderless connector, open the connector, then slide in the cut end of the strip so the copper pads line up with the contacts inside. Ensure the connector is oriented correctly so the contacts pierce through the top of the strip. Close the connector to lock it in place. Use jumper connectors instead of bending the strip for corners or gaps.

Note: *Illustrations show wiring for single-color strip.*
Follow specific wiring diagram for strip and controller type.







Typical Installation Example



T 866.811.5550 | **F** 314.972.6202
https://www.superbrightleds.com
email: commercial-sales@superbrightleds.com

Rev. V1.1 Date: 12/20/2025
Specifications are subject to change without notice.

Installation Instructions (cont.)

5. Extend the Wiring

Use the lowest gauge wire that's practical for your setup, based on the total current draw and length of the run. As a general guideline, 22 AWG is suitable for short, low-power runs, while 18 AWG or lower is recommended for longer runs or higher-powered strips. Keep the wiring short where possible and double-check polarity. Longer runs can lead to voltage drop and dimming at the far end of the strip.

Extended Power Wire Installation Example



Straight Run Layout



Center Feed Layout



Loop-back Layout



Multi-leg Layout



Voltage Drop

As current travels through the strip, resistance in the circuit causes a drop in voltage over the length of the strip, leading to dimmer light at the far end. Wire length and total power draw of the circuit influence the amount of voltage drop. To reduce it, keep wire lengths short, use thicker gauge wire, or split the power feed (center-feed or loop-back).

6. Prepare the Surface

Wipe the mounting area with alcohol or another cleaner that removes dust, oils, and residue. The strong 3M™ adhesive backing is intended for a single application.

7. Connect to Power and Test

Connect the wires from the strip or connector to the output side of the power supply or controller. Match the positive and negative sides. If you're unsure, use a multimeter. If using a dimmer or switch, install it according to the product's installation instructions. Before mounting, test the strip to make sure all sections light up properly and there are no connection issues.

8. Mount the Strip

Peel the paper from the adhesive backing and press the strip firmly into place. Work slowly from one end to the other to avoid bubbles or wrinkles. To prevent damage to the circuit, avoid bending the strip sharply or folding it over itself. Use flexible connectors for any sharp turns or difficult areas.



superbrightleds.com | Even-Glow®

Even-Glow COB LED Strips

RGB+CCT COB Strip Specifications

SPECIFICATIONS	
Model	**STN-B-F90-O35A-12Z5M-24V**
PHOTOMETRIC	
LED Color	RGB+Tunable CCT
Color Temperature	Tunable CCT (2700K-6500K)
Lumen Per Foot	340 lm/ft
Efficacy	62 lm/W
CRI	90+
Beam Angle	160°
ELECTRICAL	
Operating Voltage	24 VDC
Current Draw per Foot	232 mA/ft
Current Draw	3.8A
Wattage per Foot	5.5 W/ft
Wattage	90 Watts
Dimmer Type	PWM
MECHANICAL	
Max Run (Class 2)	16.4ft (5m)
Minimum Cut Length	42mm (1.65in.)
LEDs per Segment	35
LED Density	256 LEDs/ft
Strip Width	12mm (0.47in.)
Length	16.4ft (5m)
LED Type	COB (chip-on-board)
Input Connection Type	Pigtail
LED Lifetime	50000 hours
ENVIRONMENTAL	
IP Rating	IP20
Environmental Rating	Non-weatherproof, Suitable for Dry Locations
Ambient Operating Temperature	-20 to 60°C (-4 to 140°F)

T 866.811.5550 | **F** 314.972.6202
https://www.superbrightleds.com
email: commercial-sales@superbrightleds.com

Rev. V1.1 Date: 12/20/2025
Specifications are subject to change without notice.

Even-Glow COB LED Strips

RGB+CCT COB Strip Specifications

Dimensional Drawings





Strip Flexibility



Bending strips at sharp angles will damage circuit traces and void warranty.



Twisting strips will damage circuit traces and void warranty.



Bending strips on horizontal plane will damage circuit traces and void warranty.



Minimum bending radius ≥ 1.97in. [50mm]

T 866.811.5550 | **F** 314.972.6202
https://www.superbrightleds.com
email: commercial-sales@superbrightleds.com