KA-11 Cover

Ref. B17064F, B17064C

APPLICATION

- LED protection and light diffusion in lighting fixtures

MOUNTING

- Snapped in a dedicated profile

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	**PC**
Shape	**flat**
Maximum length on request	**393.7"**
Width	**0.5"**

Finish	Light transmission	Length	Ref
frosted	67 %	39.4"	**B17064F_1**
		78.9"	**B17064F_2**
clear	89 %	39.4"	**B17064C_1**
		78.9"	**B17064C_2**

RELATED PROFILES > ARCHITECTURAL

KOZMA
A18040

OPK-4
A00370

PDS-T
A02057

PDS-UST
A02725

KA-11 Cover

Ref. B17064F, B17064C

KLUŚ Inspiring Solutions

RELATED PROFILES > FOR MAIN LIGHTING

DES
A18030



MOD-100
A18049



MOD-50
A18047

RELATED PROFILES > FOR SCONCES AND WALL LIGHTING



LIT-L
A18033

OBIT
A04826

PLAKIN-DUO
A18069

RELATED PROFILES > ILLUMINATION OF COVES AND ARCHITECTURAL NICHES

NISA-KON
A18027



NISA-KRA
A18026



NISA-NI
A18029

NISA-PLA
A18028

POLI
A07176

RELATED PROFILES > STAIRS ILLUMINATION



POR
A06144

STEP
A04845

KA-11 Cover
Ref. B17064F, B17064C

KLUŚ Inspiring Solutions

RELATED PROFILES > TRANSPARENT PANEL ILLUMINATION

PULA
A18035

RELATED PROFILES > UNIVERSAL

45-16
A08504

45-ALU
A04023

GLAD-45
A07009

KUBIK-45
A07697

MICRO-ALU
A01888

MICRO-H
A00599

MICRO-HG
A01419

MICRO-NK
A01587

OLEK
A08505

PDS-4-PLUS
A01263

PDS-H
A09204

PDS-NK
A01588

PDS-ZM
A07696

PDS-ZM-PLUS
A02056

PDS-ZMG
A01418

KA-11 Cover

Ref. B17064F, B17064C

RELATED SYSTEMS > GENERAL LIGHTING SYSTEMS



MOD-100
18049



MOD-50
18047

PK-4
A18044+A00370