


97+ CRI Retrofit Downlight

6" Selectable CCT LED Downlight Specifications

Project _____

Type _____ Date _____



Available Model¹

DL56D-A1-SW3B14

Part Number Breakdown

Example: DL56D-A1-SW3B14

Series	Selectable CCT	Wattage
DL56D-A1 [Downlight, 5/6" Can, Dimmable]	SW3B [3000K, 4000K, or 5000K]	14 [14 Watts]

Overview

The 6" 14W LED Recessed Retrofit Downlight has a CRI of 97 for accurate and vibrant color rendering. It is ideal for bathrooms, kitchens, retail spaces, and art galleries. The downlight is constructed of a durable aluminum housing with a polycarbonate lens. The smooth trim and frosted lens diffuse the 110° beam for uniform light. Select the desired CCT using the switch on the top of the downlight. Easily install into an existing 5" or 6" recessed can lights using the E26 screw base adapter, quick link connector, and spring clips.

Features

- Highly accurate color rendering at 97 CRI
- Selectable CCT: 3000K, 4000K, and 5000K
- Easy retrofit for existing 5" to 6" recessed can lights
- Fast installation with included E26 screw base adapter
- TRIAC dimmable for smooth, flicker-free dimming

Product Details

- White aluminum housing
- Frosted polycarbonate lens
- Suitable for Wet Locations
- 75W incandescent equivalent
- TRIAC dimmable
- 120 VAC input

Certifications and Compliances

- ETL Classified - UL 1598C

ETL CLASSIFIED



Applications

- Art Galleries
- Basements
- Bathrooms
- Commercial Downlights
- Home Bars
- Home Theaters
- Kitchens
- Living Rooms
- Offices
- Residential Downlights
- Retail Shops
- Retrofit Lighting

Warranty

- 3-year warranty



¹Contact customer service if interested in other options.

97+ CRI Retrofit Downlight

6" Selectable CCT LED Downlight Specifications

SPECIFICATIONS	
Model	DL56D-A1-SW3B14
PHOTOMETRIC	
Lumens	1000 Lumens
CCT	Selectable CCT (3000K, 4000K, or 5000K)
Beam Angle	110°
CRI	97
ELECTRICAL	
Wattage	14 Watts
Current Draw	167 mA
Operating Voltage	120 VAC
Efficacy	71 lm/W
Power Factor	≥0.7
Dimmer Type	TRIAC
MECHANICAL	
Can Size	5 inch, 6 inch
Diameter	Ø6 in.
Input Connection	E26 (Medium Base)
Finish	White
Product Materials	Aluminum Housing, Frosted Polycarbonate Lens
IP Rating	IP20
Environmental Rating	Suitable for Wet Locations
Rated Life (L70)	35000 Hours
Ambient Operating Temperature	-20 to 40 °C (-4 to 104 °F)



97+ CRI Retrofit Downlight

6" Selectable CCT LED Downlight Specifications

Dimensional Drawings

