


**Important: Read all instructions prior to installation.**

## LED Mini Bollard Light



### Specifications

Environmental Specifications	
Operating Temperature	-4°–104° F (-20°–40° C)
IP Rating	IP65

### Safety and Notes

- Do not operate this product under any conditions other than those for which it is specified. Failure to observe these precautions can lead to electrical shock, product failure, or other problems.
- Turn power off from electrical panel before installation or maintenance.
- For use with outdoor, low-voltage landscape lighting systems ONLY.
- Power supply voltage must match fixture.
- Not for use with submersible or pool/spa equipment. Do not submerge in water, the product can be damaged.
- Do not modify this fixture. Any modification may render the product unsafe and void the warranty.
- Total power of fixtures should not exceed 80% of the total power rating of the connected transformer.

### Recommended Accessories

Part Number	Description
WWN-x	silicone-filled twist-on wire connector
WP14-2DB	14-gauge landscape wire
WP12-2DB	12-gauge landscape wire

### Installation Instructions

1. Turn off supply power.
2. Lay out fixtures at the desired locations.
3. Run wiring to all locations and strip back the ends in preparation for connecting to the lights.
4. Connect lights using waterproof connectors.
5. Check for proper operation.
6. If everything is working correctly, switch power back off.
7. Carefully press stake end into ground, applying pressure to the stake itself evenly and smoothly.
8. Use a shovel to carefully loosen the soil and bury the wire approximately 6 inches under the ground.

