



LED B11

3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20

Philips LED B11 candles offer energy saving ambiance with the elegant effect of incandescent candles. These designs provides light in an omnidirectional manner, giving lighting designers a long life alternative to standard incandescent sources.

Product data


General Information		Starting Time (Nom)		0.5 s
Cap-Base	E12 [Candelabra Screw]	Warm-up time to 60% light		0.5 s
Nominal lifetime	15,000 hour(s)	Power Factor (Fraction)		0.75
Switching Cycle	20,000	Voltage (Nom)		120 V
Rated Lifetime (Hours)	15,000 hour(s)	Temperature		
Lighting Technology	LED	T-Case Maximum (Nom)		122 °F
EU RoHS compliant	Yes	Controls and Dimming		
Light Technical		Dimmable		
Color Code	927-922 [CCT of 2700K-2200K]	Yes		
Luminous Flux	300 lumen	Mechanical and Housing		
Color Designation	Warm Glow(WG)	Bulb Finish		
Correlated Color Temperature (Nom)	2700 2200 K	Clear		
Luminous Efficacy (rated) (Nom)	90.00 lm/W	Bulb Material		
Color Consistency	<4	Glass		
Color rendering index (CRI)	90	Bulb Shape		
LLMF At End Of Nominal Lifetime (Nom)	70 %	B11 [B 35mm]		
Operating and Electrical		Approval and Application		
Line Frequency	50 to 60 Hz	Energy Consumption kWh/1000 h		
Input Frequency	50 to 60 Hz	- kWh		
Power Consumption	3.3 W	Energy Certifications		
Lamp Current (Nom)	35 mA	Energy Star		
Wattage Equivalent	40 W	EyeComfort		
		Yes		
		Product Data		
		Order product name		
		3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20		
		Order code		
		549568		

LED B11

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001969404
Full product name	3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20



EAN/UPC - Case	50046677549560
EAN/UPC - Product/Case	046677549565

Dimensional drawing




Product	D	C
3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20	35 mm	100 mm

Photometric data



Light Distribution Diagram - 3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20


General uniform lighting - 3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20




Spectral Power Distribution Colour - 3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20

LED B11

Lifetime



Life Expectancy Diagram - 3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20



Lumen Maintenance Diagram - 3.3B11/PER/927-922/CL/G/E12/WGX 1FB T20

