

**User Manual** 

STN-1-RGB

Important: Read all instructions prior to installation.

## **Under Cabinet LED Flexible Light Strip Kit**

#### **Included Parts**

- 1 LED Strip
- 1 RGB Controller with Wireless RF Remote(MCBRF-RGB4)
- 1 Power Supply (CPS-24V-48W)
- 1 10 ft Section of 4 Conductor 22 AWG Wire (RGB-4Wire)
- 4 Quick Connect Terminal Blocks (LQC-2)
- 14 Clamp-On Solderless Connectors (SBL-MA4P-10)
- 2 Double-Sided Adhesive Foam Pads (3M-FTP)

### **Safety and Notes**


- Product should be installed in accordance with applicable national, state, and local electrical codes.
- To reduce the risk of electric shock, ensure that the main power source is switched off and the power supply is disconnected before performing any installation or wiring procedures.
- · Product is for use in dry, indoor locations only.
- Do not connect strip or controller directly to AC power.
- Do not connect components other than those included to the power supply.
- Ensure the polarity of all connections is correct during installation.



#### **Installation Process**


#### **Preinstall Check**

Remove strip from reel and make connections to power supply and controller. Briefly turn on strip using controller power button to ensure proper operation of the strip, power supply, controller, and remote. After successful test, disconnect power supply and disconnect components.



#### Layout

Layout strip on counter below cabinets. Hold strips up under cabinets or measure to determine lengths of strip segments needed for installation. Cut strip to desired lengths ensuring all cuts are made only on marked cut lines.



#### **Strip Installation**

Attach solderless connectors (SBL-MA4P-10) to strip ends by placing the connector fully over the strip and pushing down cap until it locks in place.



Next, ensure all installation surfaces are clean and dry. Begin to remove strip's backing while adhering to bottom front edge of cabinets for optimal illumination. Press firmly to secure strips to surface.

Route wire (RGB-4Wire) for strip-to-strip connections under cabinet seams, windows, and other spaces between cabinets. Cut wire to length and attach wire ends to solderless connectors by placing the wire fully into the connector and pushing the cap down until it locks in place. Ensure the wires are connected to the correct polarity on the strip.



### Controller and Power Connection

Use the double-sided foam adhesive pads (3M-FTP) to mount the controller. Connect lead wires at the end of the strip run to the controller (MCBRF-RGB4) with terminal blocks (LQC-2).



Connect the power supply (CPS-24V-48W) to the CPS connector and apply power to check for proper operation.

<sup>1</sup>UL certification only applies to the included strip and power supply










# **User Manual**

Important: Read all instructions prior to installation.

STN-1-RGB

## **Under Cabinet LED Flexible Light Strip Kit**



<sup>1</sup>UL certification only applies to the included strip and power supply







(SBL-MA4P-10)