

**Important:** Read all instructions prior to installation.

## 4" Jeep JL/JK/JT LED Fog Lights

### Included Parts

- (2) Jeep Wrangler JL/JK/JT Fog Lights
- (2) Mounting brackets (one pre-installed)

### Specifications

Operating Voltage	12 VDC
IP Rating	IP67 waterproof
Certifications	DOT Compliant, SAE J583
Warranty	2-year
Aprox. Dimensions (Ø x D)	3.90 x 3.75 in. (99 x 95 mm)

### Installation Instructions

1. Use the trim removal tool to remove the eight (8) trim clips along the bottom edge of the lower air dam.
2. Use the 8 mm socket to remove the two (2) screws holding the air dam in place, then remove the air dam.
3. Remove the splash guard (a.k.a. bumper to fender filler panel). by using the T25 Torx driver removal tool to remove the six (6) additional screws around the edge of the splash guard. Use the 7 mm socket to remove the 7 mm screw and remove the guard.
4. Use the trim removal tool to remove the six (6) trim clips from the panel behind the bumper to expose the fog light housing.
5. Use the 7 mm socket to remove the four (4) screws that secure the fog light to the bumper. Disconnect the fog light plug from the wire harness and remove the fog light.
6. Using the four (4) original 7 mm screws and the included bracket that most closely resembles your stock fog light bracket, install the new LED fog light and connect the plug to the wire harness.



### Pre Installation Instructions

1. Read all safety notes and mounting guidelines before installing the product.
2. Verify that all parts are present and complete.
3. Verify that all power supply and charging systems comply with the specified voltage limits for the light.
4. Turn off the vehicle and disconnect the battery.

### Required Tools<sup>1</sup>

- Trim removal tool, pick tool, or flathead screwdriver
- Phillips head screwdriver
- Ratcheting socket wrench with extension
- 7 mm, 8 mm, 18 mm sockets
- T25 Torx driver

**Pro Tips:** Retain all screws and trim clips in a safe location for reinstallation. For better access turn your wheels in the direction of the side you are working on.

<sup>1</sup>Required tools may vary by model and trim level.  
Subject to change without notice.

*Important: Read all instructions prior to installation.*

## 4" Jeep JL LED Fog Light

### Instructions Cont.

7. Repeat steps 3-6 for the other fog light.
8. Reconnect the battery and apply power to test functionality.
9. Use the Phillips head screwdriver to turn the spring loaded adjustment screw for proper beam alignment.
10. Reverse steps 1-4 to complete your installation.

**Fig. 1**



<sup>1</sup>Required tools may vary by model and trim level.  
Subject to change without notice.