



- Illumination of niches and coves with a low height
- Continuous lighting angle adjustment
- Two lighting options

### APPLICATION

- decorative lighting recessed in architectural niches


### MOUNTING

- to the surface, using dedicated accessories
- easy assembly and disassembly by snapping in and out

### ADDITIONAL INFORMATION

- standard lengths of KLUŠ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŠ

### TECHNICAL DRAWING



### TECHNICAL SPECIFICATIONS

Material	aluminum
Color	■ silver anodized
Possible fixture IP	20
Possible fixture shapes	linear
Width	1"
Height	0.3"
LED gluing width A	0.4"
Number of LED strips A (0.31" wide)	1
Width of the glow	11.2 mm
Max power of a single KLUŠ LED strip	24 W/m
Lighting angle adjustment up to	90
Building type	Residential, Entertainment/ Arts, Hotel / Restaurant
Facility zone	wall lighting, niche/cove, conference room
Easy assembly and disassembly by snapping in and out	yes
The cover is cut to the length of the profile	yes
Wire out end cap	yes




Length	Ref
39.4"	A07176A_1
78.9"	A07176A_2

Wire out back of extrusion	yes
----------------------------	-----



## SAMPLE PROJECTS




## RELATED ACCESSORIES > COVERS

NAME	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.	
LIGER		PC	59 %	satin	B17037S
			21 %	black	B17037B
HS		PC	59 %	frosted	B17208F
			88 %	clear	B17208C
KA		PC	63 %	frosted	B17035M
			91 %	clear	B17035T
63 %	frosted	B17035M			
91 %	clear	B17035T			


## RELATED ACCESSORIES > END CAPS

NAME	MATERIAL	COLOR	REF.
POLI	 ABS	 gray	C24128C02


RELATED ACCESSORIES > RELATED LED > ADJUSTABLE WHITE / DIM TO WARM



**K-27/65-1920-24V**  
K-27/65-1920-24



**K-22/50-1728-24V**  
K-22/50-1728-24




**K-30/18-1770-24V**  
K-30/18-1770-24



**K-30/18-1770-010V-24V**  
K-30/18-1770-010V-24V


RELATED ACCESSORIES > RELATED LED > CRI 90+



**K-1210-24**  
K-1210-24




**K-1220-12V**  
K-1220-12




**K-1820-HD-24**  
K-HD-1820-24


RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY




**K-HE-0480-HD-24**  
K-HEHD-0480-24



**K-HE-0960-HD-24**  
K-HEHD-0960-24




**K-HE-1440-HD-24**  
K-HEHD-1440-24



**K-HE-1920-HD-24**  
K-HEHD-1920-24


RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CTT



**K-1275-RGB-24**  
K-RGB-1275-24



**K-RGBW-1530-24**  
K-RGBW-1530-24



**K-1920-120-RGB-24**  
K-RGB-1920-120-24



**K-RGB-1200-24**  
K-RGB-1200-24

RELATED ACCESSORIES > OTHER ACCESSORIES > ADDITIONAL ITEMS



GLAND  
**6x1,2**  
C24517C07

RELATED ACCESSORIES > OTHER ACCESSORIES > MOUNTING BRACKETS



MOUNTING BRACKET  
**POLI**  
C24112C10