



Available Models¹

- IT8-SW3H-C24
- IT8-SW3H-F24

Part Number Breakdown

Example: IT8-SW3H-F24

Series	CCT	Lens	Selectable Wattage
IT8 [Integrated T8 LED Fixture]	SW3H [4000K, 5000K, 6500K]	C [Clear]	24 [15W, 20W, 24W]
		F [Frosted]	

Overview

The Integrated T8 LED Tube Light delivers more brightness per fixture, which is ideal for use in garages, factories, and other larger spaces. Its slim, 48" aluminum housing and choice of frosted or clear polycarbonate lens provide smooth, uniform lighting. Wattage and CCT adjustments are made using the switches on the back of the fixture. Up to 12 fixtures can be linked using the included butt connector or an optional interconnect cable. It includes a 3-pin pigtail connector and supports an optional 48" power cable for simple plug-and-play installation. Brackets are included for easy surface mounting.

Features

- Selectable Wattage: 15W, 20W, or 24W
- Selectable CCT: 4000K, 5000K, or 6500K
- Equivalent to a 4ft 32W T8 fluorescent fixture
- Link up to 12 fixtures for extended coverage

Product Details

- Silver aluminum housing
- Frosted or clear polycarbonate lens
- Surface mount using included brackets
- 140° beam angle
- 120 VAC

Certifications and Compliances

- ETL Listed - UL 1598 and UL 153



Warranty

- 5-year warranty

Optional Accessories

- IT8-IC (6" interconnect cable)
- IT8-PC (48" power cable)



IT8 Series

Integrated T8 LED Light Fixture Specifications

Specifications

Model	IT8-SW3H-C24	IT8-SW3H-F24
OPTICAL		
Lens Color	Clear	Frosted
Lumens	1950, 2600, 3120	
Color Temperature	4000K, 5000K, 6500K, Selectable CCT	
CRI	80+	
Beam Angle	140°	
ELECTRICAL		
Wattage	15W, 20W, 24W, Selectable	
Operating Voltage	120 VAC	
Current Draw	125/165/200mA	
Efficacy	130 lm/W	
Dimmer Type	Non-Dimmable	
MECHANICAL		
Input Connection Type	3-Pin, 18AWG Pigtail	
Max Run	12	
Rated Life (L70)	50000 hours	
Length	48in. (4ft)	
Mount Type	Surface Mount	
Product Materials	Aluminum Housing, Polycarbonate Lens	
ENVIRONMENTAL		
IP Rating	IP20	
Environmental Rating	Non-weatherproof, Suitable for Dry Locations	
Ambient Operating Temperature	-20 to 50°C (-4 to 122°F)	



IT8 Series

Integrated T8 LED Light Fixture Specifications

Dimensional Drawing

