

Light efficiency:

Infinity Lumen/Watt

Output: 37847 lm

Light quality:

CRI: 82.2

Peak: 14440 cd

Color temperature:


5237 K

Product name:

ALD-50K30W-C-BRC3 Type III-M

Date and time:

4/17/2019 11:30:51 AM



Beam angle

121.3°




CIE 1931


x: 0.339

y: 0.345

Spectra



Power



Voltage: 116 V
Current: 0.000 A
Frequency: 60 Hz





T 314.743.3067

F 314.972.6202

email: commercial-sales@superbrightleds.com



www.superbrightleds.com/

Color Specifications



TM30: 79.3

CRI: 82.2 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
81.5	86.6	88.6	82.8	81.5	80.2	86.6	69.4	11.2	66.7	81.6	57.0	82.7	93.6	77.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
73.4	80.9	73.9	81.6	84.2	91.7	90.4	84.2	80.8	67.0	65.0	83.6	84.9	82.2	72.5	78.3

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
84.1	96.4	70.6	67.4	76.5	80.8	84.1	88.9	93.7	81.4	77.1	77.1	78.7	70.5	75.6

CQS: 78.6



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
5237 K	82.2	11.2	79.3	95.8	78.6	0.339	0.345	0.210	0.320	-0.0040



TM30 Report







Rf 79.3

Fidelity index Rf

Rg 95.8

Gamut index Rg


Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	73	-12%	-1%
2	81	-8%	7%
3	74	-4%	12%
4	82	0%	10%
5	84	2%	6%
6	92	3%	-1%
7	90	-3%	-4%
8	84	-8%	0%
9	81	-11%	10%
10	67	-7%	17%
11	65	1%	20%
12	84	5%	8%
13	85	10%	-2%
14	82	6%	-7%
15	72	1%	-18%
16	78	-3%	-12%



Color Evaluation Sample



Illumination



Beam intensities from 1-20m


1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
7159lx	1790lx	795lx	447lx	286lx	199lx	146lx	112lx	88lx	72lx	59lx	50lx	42lx	37lx	32lx	28lx	25lx	22lx	20lx	18lx
665.1fc	166.3fc	73.9fcd	41.6fcd	26.6fcd	18.5fcd	13.6fcd	10.4fcd	8.2fcd	6.7fcd	5.5fcd	4.6fcd	3.9fcd	3.4fcd	3fcd	2.6fcd	2.3fcd	2.1fcd	1.8fcd	1.7fcd

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
121.3°	154.8°	170.7°	68.8%	39.4%



ISO Diagrams

ISO candela diagram




10%	716 cd
20%	1432 cd
30%	2148 cd
40%	2864 cd
50%	3580 cd
60%	4296 cd
70%	5012 cd
80%	5728 cd
90%	6443 cd

Conditions:

Number of c-planes: 16

Candela at center: 7159 cd

ISO lux diagram



3%	2.15 lx
5%	3.58 lx
10%	7.16 lx
30%	21.5 lx
50%	35.8 lx

Conditions:

Number of c-planes: 16

Lux at center: 71.6 lx

*Lux distribution on a surface
when lamp is mounted at 10
meters from the surface.*




Light Planning

Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	107	102	97	92	104	99	95	91	95	91	88	91	88	85	87	85	82	80
2	96	86	78	72	93	84	77	71	81	74	69	77	72	68	74	70	66	64
3	86	74	65	57	83	72	64	57	69	62	56	66	60	54	63	58	53	51
4	78	64	54	47	75	63	53	46	60	52	45	57	50	45	55	49	44	42
5	71	56	46	39	68	55	46	38	53	44	38	51	43	37	49	42	37	35
6	64	50	40	33	62	49	39	33	47	38	32	45	38	32	43	37	31	29
7	59	44	35	28	57	44	34	28	42	34	28	40	33	27	39	32	27	25
8	55	40	31	24	53	39	30	24	38	30	24	37	29	24	35	29	24	22
9	51	36	28	22	49	36	27	21	35	27	21	33	26	21	32	26	21	19
10	48	33	25	19	46	33	25	19	32	24	19	31	24	19	30	23	19	17

LAMPS (number of lamps)

Luminaire budgetary diagram



Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
647 lm	2021 lm	3695 lm	5341 lm	6708 lm	7610 lm	7307 lm	3616 lm	775 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
34.7 lm	12.7 lm	15.1 lm	16.3 lm	15.3 lm	13.0 lm	10.9 lm	6.27 lm	2.29 lm




Road Report

LCS table


BUG rating:	B5 U3 G5	
Forward light	Lumens	Lumens %
Low(0-30):	3192.4	8.4%
Medium(30-60):	9846.1	26%
High(60-80):	5445.9	14.4%
Very high(80-90):	390.1	1%
Back light		
Low(0-30):	3192.4	8.4%
Medium(30-60):	9846.1	26%
High(60-80):	5445.9	14.4%
Very high(80-90):	390.1	1%
Uplight		
Low(90-100):	37.4	0.1%
High(100-180):	91.8	0.2%

LCS graph



Stabilization

Warmup curve



Warmup result

Warmup time:	25 min 14 sec
Warmup variation	-6.1%

Warmup conditions

Stable period:	15 min
Stable change max:	2.0%
Minimum time:	15 min

Color temperature change

CCT start	CCT change	CCT end
5133 K	+104 K	5237 K

Output change

Output start	Output change	Output end
40201 lm	-2354 lm	37847 lm




Flicker


Flicker curve (complete sampled flicker signal)



Flicker frame (frame of one flicker period)



Flicker FFT (frequency scope of flicker curve)



Flicker results:

Flicker frequency:	119.4 Hz
Flicker index:	0
Flicker percentage:	0.88 %
SVM: (Visual flicker)	0.03

Flicker conditions:

Sample rate:	40000 samples/second
--------------	----------------------

