

UFO High Bay





Features

- ◆ Lumileds SMD LED
- ◆ High efficacy of 150 lm/W
- ◆ 100–277 VAC
- ◆ 120° beam angle
- ◆ 80+ CRI
- ◆ IP69K rated so it can be washed directly
- ◆ Operating temperature of -40°–122° F (-40°–50° C)
- ◆ 5-year warranty




Dimensions



	100 W-200 W
Outlook Dimensions	Φ17.08 x 7.56 tall

Photometrics

120°



Specifications

Model	Power	Efficacy	Lumen	Input voltage	CRI	CCT
XSY-HBDU100W-50KSV-DNCB	100W	150LM/W	15000lm	100-277 VAC	80+	5000K
XSY-HBDU150W-50KSV-DNCB	150W		22500lm			
XSY-HBDU200W-50KSV-DNCB	200W		30000lm			

Ordering Guide

For example: XSY - HBD Q XXW - XXK AA - YZ T

Brand	Product name	Region	Power	CCT	Input voltage	Mounting	Sensor	Efficacy
XSY	HBD	Q	XXW	XXK	AA	Y	Z	T
XSY	HBD	U America	100W 150W 200W	50K 5000K	SV 100-277VAC	D Suspending G Pendant	NC Without Sensor	B 150lm/w