

**Important: Read all instructions prior to installation.**

## LED Tailgate Light Bar

### Warning


The installation of this kit is recommended to be installed by a licensed professional. The improper installation of this kit will void all warranties.

### Installation Instructions

1. First using a tape measurer, measure the lip under your vehicle tailgate to ensure there is enough clearance to mount your LED Tailgate Light Bar.
2. Clean surface with 90% or greater Isopropyl alcohol prior to installation (not included).
3. Apply 3M Adhesion Promoter (06396 Available at [superbrightleds.com](http://superbrightleds.com)).
4. Remove adhesive backing film and attach LED Tailgate Light Bar to surface.
5. Run power wire with flat 4 pin connector behind your bumper and to your vehicles flat 4 pin connection. You may need to secure the slack in the wire so that it does not hang below bumper.
6. Locate power wire for reverse lights and attach reverse wire with splice tap (IDC-2218 available at [superbrightleds.com](http://superbrightleds.com))

### Wiring Diagram

Wire Color	Electrical Connection
Brown Wire (A)	Ground (-12V DC)
White Wire (B)	Running Light (+12V DC)
Yellow Wire (C)	Left Turn Signal (+12V DC)
Green Wire (D)	Right Turn Signal (+12V DC)
Orange Wire (R)	Reverse Wire (+12V DC)



Rev Date: V1 06/20/2017

4400 Earth City Expy, St. Louis, MO 63045

• 866-590-3533

• [superbrightleds.com](http://superbrightleds.com)